GUARD HIGH [S7L HRO SR ESD LG]

UNISEX: 72238 BLACK

SIZE: EU 36-48, UK 3-13

S7L HRO SR ESD LG CE LE EN ISO 20345:2022 [S7L HRO SR ESD LG]







Leather / Mesh



Recycled polyester lining



WATER RESISTANCE of the whole footwear to keep your feet dry



Metal Free



COMPOSITE SAFETY TOE - 200 joules



MVT Test Method EN ISO 20345 - 41.2 mg/cm² ISO 16604 Resistant to blood borne pathogens

Breathable lining material made from 100% recycled plastic bottles



4SG - FOUR SEASONS GRIP

- Optimum slip resistance in all weathers and all types of soiling
- Provides protection on surfaces with ice / liquids / fuels / oil





EXTREMELY SLIP-RESISTANT SFC OUTSOLE

Exceeds the industry norm SR according to EN ISO 20344:2021 slip resistance test



TRIPGUARD TO PROTECT AGAINST FALLS

- Allows ease of movement between different
- Added depth for improved durability and
- Larger surface covered by the outsole provides better slip-resistance

CLOG-RESISTANT traction lugs are widely spaced to prevent dirt and debris getting stuck in the outsole

Weight (per shoe): 775 grams (based on size 42)

8" or 20.3 cm shaft height



DATA GUIDE


EN ISO 20345:2022 [S7L HRO SR ESD LG]

Upper Material: Leather

Lining Material: Recycled Polyester

Outsole Material: Rubber

TESTING THE SLIP RESISTANCE OF OUR 4SG FOUR SEASONS GRIP OUTSOLE [EN ISO 20344:2021]




Click or scan QR code to view certificate

SFC slip resistance Industry standard

Slip resistance test according to EN ISO 20344:2021, December 2022; on a scale of 0.0 (without slip resistance ed floors). All SFC shoes are fitted with the patented Tested product: Darver/Callan Mid (62209/62204)

TESTING THE SLIP RESISTANCE OF OUR 4SG FOUR SEASONS GRIP OUTSOLE ON ICE [SATRA TM144:2021]



onducted by Intertek Testing Services Shenzhen Ltd., in to 1.0 (very high level of slip resistance, e.g. on dry car-



Guard Mid: 72237